CSCI 678: Theoretical Machine Learning
Homework 3

Fall 2026, Instructor: Haipeng Luo

This homework is due on **11/01** *at 11:59pm. See course website for more instructions on finishing and submitting your homework as well as the late policy. Total points: 50*

1. (**Hedge**) (8pts) Consider learning over a finite class of binary classifier $\mathcal{F} \subset \{-1,+1\}^{\mathcal{X}}$ with respect to the 0-1 loss using Hedge. Under the realizable assumption $\inf_{f\in\mathcal{F}} \sum_{t=1}^{n} \mathbf{1}\{f(x_t) \neq y_t\} = 0$, prove that Hedge with learning rate $\eta = 1/2$ makes at most $4\ln|\mathcal{F}|$ mistakes in expectation. Hint: use Lemma 1 of Lecture 7. (Note that this is similar to the guarantee of Halving, but achieved via a proper algorithm this time.)

   Proof. Similarly to the proof of Theorem 1 of Lecture 7, to apply Lemma 1 we set $K = |\mathcal{F}|$, rename the elements of $\mathcal{F}$ by $1,\dots,K$, and set $\ell_t(i) = \ell(i, z_t)$, so that Hedge exactly samples $\widehat{y}_t$ according to p_t as defined in Lemma 1. The realizable assumption becomes $\min_{i^\star} \sum_{t=1}^{n} \ell_t(i^\star) = 0$, and thus Lemma 1 states

$$\sum_{t=1}^{n} \langle p_t, \ell_t \rangle \leq \frac{\ln K}{\eta} + \eta \sum_{t=1}^{n} \sum_{i=1}^{K} p_t(i)\ell_t^2(i).$$

   Since $\ell_t(i)$ is either 0 or 1, the term $\sum_{i=1}^{K} p_t(i)\ell_t^2(i)$ is in fact equal to $\langle p_t, \ell_t \rangle$. Therefore, rearranging gives

$$\sum_{t=1}^{n} \langle p_t, \ell_t \rangle \leq \frac{\ln K}{(1-\eta)\eta}.$$

   The left hand side of the above inequality is exactly the expected number of mistakes made by Hedge, and the right hand side is $4\ln|\mathcal{F}|$ with the specific choice of learning rate $\eta = 1/2$, which finishes the proof. □

2. (**Perceptron and sequential fat-shattering dimension**) Recall the sequential fat-shattering dimension $\mathrm{sfat}(\mathcal{F}, \alpha)$ defined in Lecture 6. Let $\mathcal{X} = B_2^d$ and $\mathcal{F} = \left\{ f_\theta(x) = \langle \theta, x \rangle \mid \theta \in B_2^d \right\}$. In this exercise, you will prove $\mathrm{sfat}(\mathcal{F}, \alpha) \le \frac{16}{\alpha^2}$ (which is independent of d) for any $\alpha > 0$, using an indirect approach that leverages the guarantee of the Perceptron algorithm.

   More specifically, suppose that $\boldsymbol{x}$ is a $\mathcal{X}$-valued tree of depth n that is α-shattered by $\mathcal{F}$, with witness $\boldsymbol{y}$, a $[-1, +1]$-valued tree. Now, imagine running Perceptron in the following problem instance in $\mathbb{R}^{d+1}$:

> Let $\theta' = \mathbf{0} \in \mathbb{R}^{d+1}$. For $t = 1, \dots, n$:
> - Environment reveals example $x'_t = \frac{1}{\sqrt{2}}(\boldsymbol{x}_t(y'_{1:t-1}), \boldsymbol{y}_t(y'_{1:t-1})) \in B_2^{d+1}$.
> - Perceptron algorithm predicts $s_t = \mathrm{sign}(\langle x'_t, \theta' \rangle) = \begin{cases} +1 & \text{if } \langle x'_t, \theta' \rangle \ge 0, \\ -1 & \text{else.} \end{cases}$
> - Environment reveals $y'_t = -s_t$, forcing Perceptron to make an update $\theta' \leftarrow \theta' + y'_t x'_t$.

   Note that the environment is valid even though it seemingly decides the label y'_t after seeing the algorithm's prediction s_t, since Perceptron is a deterministic algorithm (and thus $x'_{1:n}$ and $y'_{1:n}$ are in fact all fixed ahead of time).

   (a) (5pts) Prove that the data constructed above satisfy the γ-margin assumption (Assumption 1 of Lecture 7) with $p = q = 2$. In other words, find a specific value of $\gamma > 0$ and show that there exists $\theta'_\star \in B_2^{d+1}$ such that $y'_t \langle \theta'_\star, x'_t \rangle \ge \gamma$ holds for all $t = 1, \dots, n$.

   Proof. Since $\boldsymbol{x}$ is α-shattered by $\mathcal{F}$, there exists $\theta \in B_2^d$ such that

$$y'_t(\langle \theta, \boldsymbol{x}_t(y'_{1:t-1}) \rangle - \boldsymbol{y}_t(y'_{1:t-1})) \ge \frac{\alpha}{2}$$

   holds for all $t = 1, \dots, n$. This is equivalent to $y'_t \langle \theta'_\star, x'_t \rangle \ge \gamma$ if we let $\theta'_\star = \frac{1}{\sqrt{2}}(\theta, -1) \in B_2^{d+1}$ and $\gamma = \frac{\alpha}{4}$, showing that the margin assumption is satisfied with $\gamma = \frac{\alpha}{4}$. □

   (b) (4pts) Use the guarantee of Perceptron (that is, Theorem 4 of Lecture 7) to conclude $\mathrm{sfat}(\mathcal{F}, \alpha) \le \frac{16}{\alpha^2}$.

   Proof. Since the margin assumption is satisfied with $\gamma = \frac{\alpha}{4}$, Theorem 4 of Lecture 7 shows that Perceptron makes at most $1/\gamma^2 = 16/\alpha^2$ mistakes. On the other hand, the construction is such that Perceptron makes a mistake in every round, which must imply $n \le 16/\alpha^2$. Since $\boldsymbol{x}$ is an arbitrary tree α-shattered by $\mathcal{F}$, this further implies $\mathrm{sfat}(\mathcal{F}, \alpha) \le \frac{16}{\alpha^2}$. □

3. (**Winnow**) When the γ-margin assumption holds with $p = q = 2$, we have seen that Perceptron makes at most $\frac{1}{\gamma^2}$ mistakes for an online binary classification problem. In this exercise, you will prove a similar result when the γ-margin assumption holds with $p = 1$ and $q = \infty$, using a different algorithm called *Winnow*. To show this, we first consider the following generalization of Perceptron, defined in terms of some *link function* $g : \mathbb{R}^d \to \mathbb{R}^d$.

Algorithm 1: A generalization of Perceptron

Let $\theta = \mathbf{0}$. For $t = 1, \ldots, n$:

- Receive x_t and predict $s_t = \text{sign}(\langle x_t, g(\theta) \rangle)$.
- Receive $y_t \in \{-1, +1\}$. If $y_t \neq s_t$, update $\theta \leftarrow \theta + y_t x_t$.

It is clear that when instantiated with g being the identity mapping $g(\theta) = \theta$, Algorithm 1 is exactly the Perceptron algorithm. Below, we will see that the Winnow algorithm is also an instance of Algorithm 1 but with a different link function. Throughout, we assume $x_t \in B_\infty^d$, that is, $\|x_t\|_\infty \leq 1$, for all t.

(a) Consider running Algorithm 1 with link function $g(\theta) = \exp(\eta\theta)$ and some parameter $\eta > 0$ (where the exponentiation is applied coordinate-wise to the vector $\eta\theta$). Let's call this the simplified Winnow algorithm.

i. (5pts) Find a sequence of loss vectors $\ell_1, \ldots, \ell_n \in [-1, +1]^d$ such that the prediction of simplified Winnow $s_t = \text{sign}(\langle x_t, g(\theta) \rangle)$ can be equivalently written as $s_t = \text{sign}(\langle x_t, p_t \rangle)$, where $p_t \in \Delta(d)$ is a distribution such that

$$p_t(i) \propto \exp\left(-\eta \sum_{\tau < t} \ell_\tau(i)\right), \quad \text{for all } i = 1, \ldots, d.$$

Proof. The loss vector ℓ_t should be $-\mathbf{1}\{y_t \neq s_t\} y_t x_t$ (which is in $[-1, +1]^d$ since $\|x_t\|_\infty \leq 1$). This is because at the beginning of round t, the vector θ is $\sum_{\tau < t} \mathbf{1}\{y_\tau \neq s_\tau\} y_\tau x_\tau$, and thus

$$s_t = \text{sign}(\langle x_t, g(\theta) \rangle) = \text{sign}\left(\left\langle x_t, \frac{g(\theta)}{\|g(\theta)\|_1} \right\rangle\right) = \text{sign}(\langle x_t, p_t \rangle).$$

□

ii. (10pts) Based on the reformulation of the last question, apply Lemma 1 of Lecture 7 to show that as long as $\eta \leq 1$, we have for any $\theta^\star \in \Delta(d)$:

$$\sum_{t=1}^n \mathbf{1}\{y_t \neq s_t\} y_t \langle \theta^\star, x_t \rangle \leq \frac{\ln d}{\eta} + \eta M,$$

where $M = \sum_{t=1}^n \mathbf{1}\{y_t \neq s_t\}$ is the total number of mistakes made by the simplified Winnow algorithm.

Proof. Since $\eta \leq 1$ and $\ell_t(i) \in [-1, 1]$, the condition $\eta \ell_t(i) \geq -1$ of Lemma 1 of Lecture 7 holds. Directly applying the lemma then shows for any $i^\star \in \{1, \ldots, d\}$,

$$\sum_{t=1}^n \langle p_t, \ell_t \rangle - \sum_{t=1}^n \ell_t(i^\star) \leq \frac{\ln d}{\eta} + \eta \sum_{t=1}^n \sum_{i=1}^d p_t(i) \ell_t(i)^2,$$

which means for any $\theta^\star \in \Delta(d)$:

$$\sum_{t=1}^n \langle p_t, \ell_t \rangle - \sum_{t=1}^n \langle \theta^\star, \ell_t \rangle \leq \frac{\ln d}{\eta} + \eta \sum_{t=1}^n \sum_{i=1}^d p_t(i) \ell_t^2(i).$$

We now plug in the definition of ℓ_t and bound each term. First, we have

$$\sum_{t=1}^n \langle p_t, \ell_t \rangle = \sum_{t=1}^n -\mathbf{1}\{y_t \neq s_t\} y_t \langle p_t, x_t \rangle \geq 0,$$

where the inequality is because whenever $\mathbf{1}\{y_t \neq s_t\} = 1$, we must have $y_t \langle p_t, x_t \rangle \leq 0$ since $s_t = \text{sign}(\langle p_t, x_t \rangle)$. Second, we have by definition.

$$-\sum_{t=1}^{n} \langle \theta^\star, \ell_t \rangle = \sum_{t=1}^{n} \mathbf{1}\{y_t \neq s_t\} y_t \langle \theta^\star, x_t \rangle$$

Finally, since $x_t^2(i) \leq 1$, we have

$$\sum_{t=1}^{n}\sum_{i=1}^{d} p_t(i)\ell_t^2(i) \leq \sum_{t=1}^{n}\sum_{i=1}^{d} p_t(i)\mathbf{1}\{y_t \neq s_t\} = M.$$

Combining all terms finishes the proof. □

iii. (3pts) Consider the following assumption that is slightly stronger than the original γ-margin assumption with $p = 1$ and $q = \infty$:

$$\text{there exists } \theta^\star \in \Delta(d) \text{ such that } y_t \langle \theta^\star, x_t \rangle \geq \gamma \text{ for all } t. \tag{1}$$

Prove that under this assumption, the total number of mistakes M made by the simplified Winnow algorithm is at most $\frac{4 \ln d}{\gamma^2}$ when $\eta = \frac{\gamma}{2} \leq 1$.

Proof. Using the assumption and continuing with the result from the last question, we have

$$\gamma M \leq \sum_{t=1}^{n} \mathbf{1}\{y_t \neq s_t\} y_t \langle \theta^\star, x_t \rangle \leq \frac{\ln d}{\eta} + \eta M.$$

Rearranging and plugging the value of η proves the claim. □

(b) Now consider the original γ-margin assumption, that is:

$$\text{there exists } \theta^\star \in B_1^d \text{ such that } y_t \langle \theta^\star, x_t \rangle \geq \gamma \text{ for all } t. \tag{2}$$

To deal with this more general case, we will run Algorithm 1 using a different link function $g(\theta) = \exp(\eta\theta) - \exp(-\eta\theta)$ (again, the exponentiation is coordinate-wise). This is the (actual) Winnow algorithm.

i. (5pts) Prove that the Winnow algorithm makes the same predictions as one would obtain by running the simplified Winnow algorithm over examples $x'_t = (x_t, -x_t) \in B_\infty^{2d}$ and $y'_t = y_t$ for $t = 1, \ldots, n$.

Proof. When running the simplified Winnow over $x'_t = (x_t, -x_t) \in B_\infty^{2d}$ and $y'_t = y_t$, the vector θ at the beginning of round t, renamed as θ' to avoid confusion, is $\sum_{\tau<t} \mathbf{1}\{y_\tau \neq s_\tau\} y_\tau (x_\tau, -x_\tau)$, which is equal to $(\theta, -\theta)$, where θ here is now the weight vector of the actual Winnow algorithm at the beginning of round t. Therefore, the two algorithms make the exact same prediction:

$$\text{sign}(\langle (x_t, -x_t), \exp(\eta\theta') \rangle) = \text{sign}(\langle x_t, \exp(\eta\theta) \rangle - \langle x_t, \exp(-\eta\theta) \rangle) = \text{sign}(\langle x_t, g(\theta) \rangle).$$

□

ii. (7pts) Under the margin assumption Equation (2), further prove that the examples $(x'_{1:n}, y'_{1:n})$ defined above satisfy Equation (1) for some margin γ', that is, there exists $\theta' \in \Delta(2d)$ such that $y'_t \langle \theta', x'_t \rangle \geq \gamma'$ for all t.

Proof. Define $\theta'' = (\theta_+^\star, \theta_-^\star) \in \mathbb{R}^{2d}$ where $\theta^\star$ is from Equation (2), $\theta_+^\star$ is obtained by zeroing out all coordinates of $\theta^\star$ that are negative, and similarly $\theta_-^\star$ is obtained by zeroing out all coordinates of $-\theta^\star$ that are negative. Further define $\theta' \in \Delta(2d)$ by normalizing the coordinates of θ'' (which are all nonnegative). Now, the condition $y_t \langle \theta^\star, x_t \rangle \geq \gamma$ from Equation (2) implies

$$\gamma \leq y_t \langle \theta^\star, x_t \rangle = y_t \langle \theta'', (x_t, -x_t) \rangle = y'_t \|\theta''\|_1 \langle \theta', x'_t \rangle \leq y'_t \langle \theta', x'_t \rangle,$$

where the last inequality is due to $\|\theta''\|_1 = \|\theta^\star\|_1 \leq 1$. Therefore, the margin assumption of Equation (1) is satisfied with the same margin $\gamma' = \gamma$. □

iii. (3pts) Finally, under the margin assumption Equation (2), use the result from Question (a)(iii) to provide a bound on the total number of mistakes made by the Winnow algorithm when $\eta = \frac{\gamma}{2}$.

Proof. Since Winnow is the same as the simplified Winnow run on a problem in $\mathbb{R}^{2d}$ that satisfies the assumption Equation (1) with margin γ, the total number of mistakes is at most $\frac{4\ln(2d)}{\gamma^2}$. □